HIKVISION

HIK-IP6322WD-I
2MP WDR EXIR Turret Network Camera

- Up to 2 megapixel high resolution
- Full HD1080p video
- Dual stream
- 2.8mm/4mm/6mm fixed lens
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- Backlight Compensation
- DC12V & PoE
- Support H.264+
- High performance EXIR LED
- Up to 30m IR range
- IP67 weather-proof protection
- 3-axis adjustment
- Dual stream

Camera Accessories

Wall Mount

DS-1273ZJ-130-TRL

Junction Box

DS-1280ZJ-M

Inclined Ceiling Mount

DS-1281ZJ-M

Corner mount

DS-1276ZJ

Vertical Pole mount

DS-1275ZJ

HIK-IP6322WD-I
2MP WDR EXIR Turret Network Camera

Specification

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/10,000 s
Lens	2.8mm, 4mm, 6mm @ F2.0 angle of view: 109.4°(2.8mm), 90°(4mm), 53.9°(6mm)
Lens Mount	M12
Day &Night	IR cut filter with auto switch
DNR	3D DNR
Wide Dynamic Range	120dB
Angle Adjustment	Pan:0°~ 360°, Tilt: 0°~ 75°, Rotation: 0°~ 360°
Compression Standard	
Video Compression	H.264 / MJPEG/H.264+
H.264 Type	Main Profile
Video Bit Rate	32 Kbps ~ 16 Mbps
Dual streams	Support
Image	
Max. Resolution	1920 × 1080
Max Frame Rate	50Hz:Main stream:25fps(1920×1080),25fps(1280×960),25fps(1280×720)Sub stream:25fps(352×288),25fps(640×360) 60Hz: Main stream:30fps (1920×1080), 30fps(1280×960), 30fps(1280×720) Sub stream: 30fps(352×240),30fps(640×360)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
BLC	Support, zone configurable
ROI Codec	Support
Network	
Network Storage	NAS (Support NFS,SMB/CIFS), ANR
Detection	Intrusion detection, Line crossing detection, Motion detection, Dynamic analysis
Alarm Trigger	Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General Function	Anti-Flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet port

HIK-IP6322WD-I
2MP WDR EXIR Turret Network Camera

General	
Operating Conditions	-30 ℃ ~ 60 ℃ (-22 ℉ ~ 140 ℉), Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 25%, PoE (802.3af)
Power Consumption	Max. 5.5W (Max. 7.5W with ICR on)
Material	Housing: Plastic; Body & Dome Cover: Metal
IR Range	Approx. 30 meters
Ingress Protection	IP67
Dimensions	Φ127×97.5 (5.0” × 3.8”)
Weight	670g (1.5 lbs)

Order Models

HIK-IP6322WD-I

Dimensions